

Technical data sheet

ALBERDINGK® AC 75222

Characteristic:

Aqueous, fine disperse, medium viscous copolymer-dispersion of acrylic acid esters and without plasticizers (APEO-free).

		According to:
%	67.0 - 69.0	ISO 3251
		1.0 g weighed quantity at 105°C
	5.0 - 6.0	ISO 976
mPas	2000 - 5000	ISO 2555, Brookfield RVT
		Spindle 3/rpm 20/factor 50
		According to:
°C	ca. 0	
g/cm3	1.0 - 1.1	ISO 2811-1
°C	ca46	DSC, heating rate 20 K/min
	mPas °C g/cm3	5.0 - 6.0 mPas 2000 - 5000 °C ca. 0 g/cm3 1.0 - 1.1

Properties:

Films formed from this dispersion are permanently tacky, and extremely heat resistance.

Applications:

Suitable for producing adhesives for labels, sheets and tapes.

Latest update 29.01.2014

Alberdingk Boley GmbH | Düsseldorfer Str. 53 | 47829 Krefeld | Germany
Phone +49 2151 528-0 | Fax +49 2151 573643 | info@alberdingk-boley.de | www.alberdingk-boley.de

Page 1 of 2

Alberdingk Boley, Inc. | Greensboro, NC, USA | www.alberdingkusa.com Alberdingk Resins (Shenzhen) Co.Ltd. | Shenzhen City, P.R. China | www.alberdingkchina.com

The details contained herein are based on our present state of technology and shall inform on our products and their application possibilities. A lawful binding assurance of certain attributes or the suitability for a concrete operation purpose cannot be derived from thisinformation. Industrial property rights are to be considered if required.



Technical data sheet

ALBERDINGK® AC 75222

Storage:

In originally closed containers ALBERDINGK-dispersions are stable when stored at 20°C for 6 months after delivery date. The recommended temperature-range for storage is 5 - 30°C. Freezing or storage at higher temperatures than 30°C, can affect the viscosity or the average particle size and finally lead to a sedimentation or coagulation. A contamination with bacteria, fungi or algae can damage the product irreversibly. The product is only preserved for the transport. For a longer storage time, we recommend to add additional preservative. A warranty for the sterility after storage can not be granted. ALBERDINGK BOLEY GmbH assures that the data mentioned under "specification" are stable for 6 months after delivery date, if the product is stored under the recommended conditions. A longer storage does not mean that the product is not usable anymore, but we recommend to check the specification data before use. A warranty after 6 months of storage can not be given by ALBERDINGK BOLEY GmbH. The product should be stirred well before use.

Packaging:

plastic drums (120 kg) one-way container (approx. 1000 kg) as bulk in tank cars, by agreement.

Safety:

For further information on product safety please refer to the current safety data sheet.

Notice:

* General information - the values can not be considered as part of the product specification.

Latest update 29.01.2014

Alberdingk Boley GmbH | Düsseldorfer Str. 53 | 47829 Krefeld | Germany Phone +49 2151 528-0 | Fax +49 2151 573643 | info@alberdingk-boley.de | www.alberdingk-boley.de

Page 2 of 2

Alberdingk Boley, Inc. | Greensboro, NC, USA | www.alberdingkusa.com Alberdingk Resins (Shenzhen) Co.Ltd. | Shenzhen City, P.R. China | www.alberdingkchina.com