

Preliminary technical data sheet

ALBERDINGK® LUR 10 VP

Characteristic:

Oxidative drying, waterbased, anionic, solvent free, aliphatic polyurethane dispersion based on linseed oil.

Specification: Solids content	%	34.0 - 36.0	According to: ISO 3251 0.5 g weighed quantity at 105°C
pH- value Viscosity	mPas	7.0 - 9.0 20 - 200	ISO 976 ISO 2555, Brookfield RVT Spindle 1/rpm 20/factor 5
Further typical data*:	°C	ca. 21	According to:
Density Solvent-free	g/cm3	1.0 - 1.1	ISO 2811-1

Applications:

For high quality hardwood floor and furniture coatings with:

- outstanding wood warming "Anfeuerung", similar to solvent based oil modified coatings

- very fast hardness development
- high gloss
- excellent chemical resistance
- very good sanding properties
- very good adhesion

Latest update	Alberdingk Boley GmbH Düsseldorfer Str. 53 47829 Krefeld Germany			
22.12.2022	Phone +49 2151 528-0 Fax +49 2151 573643 info@alberdingk-boley.de www.alberdingk-boley.de			
Page 1 of 2	Alberdingk Boley, Inc. Greensboro, NC, USA www.alberdingkusa.com			
2	Alberdingk Resins (Shenzhen) Co.Ltd. Shenzhen City, P.R. China www.alberdingkchina.com			
	The details contained herein are based on our present state of technology and shall inform on our products and their application possibilities. A lawful binding assurance of certain attributes or the suitability for a concrete operation purpose cannot be derived from thisinformation. Industrial property rights are to be considered if required.			



Preliminary technical data sheet

ALBERDINGK® LUR 10 VP

Storage:

In originally closed containers ALBERDINGK-dispersions are stable when stored at 20°C for 6 months after delivery date. The recommended temperature-range for storage is 5 - 30°C. Freezing or storage at higher temperatures than 30°C, can affect the viscosity or the average particle size and finally lead to a sedimentation or coagulation. A contamination with bacteria, fungi or algae can damage the product irreversibly. The product is only preserved for the transport. For a longer storage time, we recommend to add additional preservative. A warranty for the sterility after storage can not be granted. ALBERDINGK BOLEY GmbH assures that the data mentioned under "specification" are stable for 6 months after delivery date, if the product is stored under the recommended conditions. A longer storage does not mean that the product is not usable anymore, but we recommend to check the specification data before use. A warranty after 6 months of storage can not be given by ALBERDINGK BOLEY GmbH. The product should be stirred well before use.

Packaging:

plastic drums (120 kg) one-way container (approx. 1000 kg) as bulk in tank cars, by agreement.

Safety:

For further information on product safety please refer to the current safety data sheet.

Notice:

property rights are to be considered if required.

* General information - the values can not be considered as part of the product specification.

 Latest update
 Alberdingk Boley GmbH | Düsseldorfer Str. 53 | 47829 Krefeld | Germany

 22.12.2022
 Phone +49 2151 528-0 | Fax +49 2151 573643 | info@alberdingk-boley.de | www.alberdingk-boley.de

 Page 2 of 2
 Alberdingk Boley, Inc. | Greensboro, NC, USA | www.alberdingkusa.com

 Alberdingk Resins (Shenzhen) Co.Ltd. | Shenzhen City, P.R. China | www.alberdingkchina.com

 The details contained herein are based on our present state of technology and shall inform on our products and their application possibilities. A lawful binding assurance of certain attributes or the suitability for a concrete operation purpose cannot be derived from thisinformation. Industrial