

# Technical data sheet

## ALBERDINGK® U 9380

### Characteristic:

Aqueous, colloidal, anionic, low viscous dispersion of an aliphatic polyester-polyurethane without free isocyanate groups.

### Specification:

Solids content	%	31.0 - 34.0
----------------	---	-------------

### According to:

ISO 3251  
0.5 g weighed quantity at  
105°C

pH- value		7.5 - 9.0
-----------	--	-----------

ISO 976

Viscosity	mPas	10 - 250
-----------	------	----------

ISO 2555, Brookfield RVT  
Spindle 1/rpm 20/factor 5

### Further typical data\*:

MFFT	°C	ca. 25
------	----	--------

### According to:

Density	g/cm <sup>3</sup>	1.0 - 1.1
---------	-------------------	-----------

ISO 2811-1

Solvent-free

### Film properties\*:

Blocking point	°C	ca. 140
----------------	----	---------

### According to:

Pendulum hardness (König)	s	ca. 130
---------------------------	---	---------

ISO 1522

### Applications:

Coating systems with good chemical resistance.

Applications: plastic and wood coatings as well as good compatibility with acrylic dispersions.

# Technical data sheet

## ALBERDINGK® U 9380

### Storage:

In originally closed containers ALBERDINGK-dispersions are stable when stored at 20°C for 6 months after delivery date. The recommended temperature-range for storage is 5 - 30°C. Freezing or storage at higher temperatures than 30°C, can affect the viscosity or the average particle size and finally lead to a sedimentation or coagulation. A contamination with bacteria, fungi or algae can damage the product irreversibly. The product is only preserved for the transport. For a longer storage time, we recommend to add additional preservative. A warranty for the sterility after storage can not be granted. ALBERDINGK BOLEY GmbH assures that the data mentioned under "specification" are stable for 6 months after delivery date, if the product is stored under the recommended conditions. A longer storage does not mean that the product is not usable anymore, but we recommend to check the specification data before use. A warranty after 6 months of storage can not be given by ALBERDINGK BOLEY GmbH. The product should be stirred well before use.

### Packaging:

plastic drums (120 kg)  
one-way container (approx. 1000 kg)  
as bulk in tank cars, by agreement.

### Safety:

For further information on product safety please refer to the current safety data sheet.

### Notice:

\* General information - the values can not be considered as part of the product specification.