

Overview

ALBERDINGK® AC 25352

Product number: 000000000000274146

Description

Aqueous, fine disperse copolymer dispersion (surfactant type) without plasticizers and protective colloids.

Because of the high water-resistance suitable for anti-corrosion coatings. In combination with ALBERDINGK polyurethane dispersions e. g. ALBERDINGK® U 3251 and ALBERDINGK® U 8001 also recommended for wood, cork and plastic coatings.

Product information

Minimum film forming temperature (MFFT) (°C):	20
Multi phase:	No
Self crosslinking (SXL):	No
Solids content:	50.0 - 52.0
Viscosity (Brookfield RVT) (mPas):	300 - 800
pH-value :	7.0 - 8.0
Applications:	• Coating for electroplated surfaces pH neutral • Flooring • Flooring > Concrete • Metal • Metal > DTM • Packaging • Packaging > Paper & cardboard • Packaging > Plastic • Packaging with food contact • Packaging with food contact > Plastic • Plastic • Plastic > ABS • Plastic > PA 6 (Perlon) • Plastic > PA 6.6 (Nylon) • Plastic > PC • Plastic > PET • Plastic > PS • Plastic > PVC flexible • Plastic > PVC rigid • Plastic > Xenoy CL 100 (PBT+PC)