

New products highlights



- Low odour
- Excellent wet scrub resistance
- For preservative free/silicate paints
- MFFT: 4°C



Alberdingk[®] SC 4800 VP

- MFFT 20°C
- Low odour
- Excellent water and alkali resistance
- Good flexibility in sealant



Alberdingk[®] AC 2022 VP

- High solids pure acrylic
- •Ammonia free
- Silicate compatible
- Excellent wet srub resistance
- Low dirt pickup



Alberdingk[®] AC 2006 VP

- Exceptional efflorescence resistance
- Excellent dirt pickup resistance
- Outstanding colour stability
- No surfactant leaching

While the descriptions, data and information (collectively, the "Information") contained herein, or otherwise made available to or used by a customer, potential customer and/or user (each, a "User"), represent our current state of technology and are presented in good faith and believed to be accurate, they are provided for guidance purposes only. Alberdingk Boley itself and on behalf of all of its past, current and future affiliated and related companies and entities (hereinafter referred to as "AB") make no warranties (expressed or implied), as to the Information's accuracy, sufficiency, adequacy or freedom from defect and assumes no liability in connection with any use of the Information. The Information is not intended to assure certain characteristics of AB's products and their suitability of particular application fields and/or uses, as many factors may affect processing, application and/or use. Any User of AB's products is responsible for determining the suitability of such products for its particular application. No express or implied warranty is made by AB of the merchantability, suitability, fitness for a particular purpose, freedom from patent infringement or otherwise of any product or service. Any existing intellectual/industrial property rights must be observed. AB will not be liable to any User for any damages including, without limitation, any special, incidental or consequential damages. In no case shall any Information provided to a User be considered part of AB's terms and conditions of sale.



New products highlights



Alberdingk[®] AC 3686 VP

- Exceptional hand fat resistance
- High solid content for broad formulation latitude
 - Clear in the can
- Very good chemical resistance
- Long open time
- Very good wet adhesion



Alberdingk[®] Ren AC 8003 VP *

- As biobased alternative to Alberdingk[®] AC 2003
- Good weathering and water resistance
- Low dirt pick up
 MFFT 3°C, low tack

Alberdingk[®] U 8500 *

- 1K and 2K parquet varnishes
- Easy to formulate
- No discolouration in overlapping zones



Alberdingk[®] U 355 VP

- •1K and 2K adhesives for heatseal applications
- Excellent adhesion properties
- High hydrolysis resistance
- Low activation temperature

* Don't miss our further products based on renewable resources, further information: see our <u>website</u>

For further information, please contact us:

Alberdingk Boley GmbH

Düsseldorfer Str. 53 | 47829 Krefeld | Germany Tel.: +49 2151/528-0 | mailto: <u>info@alberdingk-boley.de</u>



or follow the QR-code: