

Construction application highlights



Alberdingk® AS 2110 VP

- Silane modified styrene acrylic
- MFFT 0°C / ammonia-free for EC1 plus
- Superior wet adhesion, even on glazed tiles
- For primers, ETICS
- Cement-free tile adhesives



Alberdingk® AS 2120 VP

- Silane modified styrene acrylic
- MFFT 17°C, neutralised with ammonia
- High water resistance
- Superior wet adhesion



Alberdingk® SC 4450

- MFFT 18°C
- Universal and economic binder
- Excellent water resistance and adhesion properties
- Low odour



Alberdingk® SC 4800 VP

- MFFT 20°C
- Low odour
- Excellent water and alkaline resistance
- Good flexibility in sealants
- Ammonia-free

Construction application highlights



Alberdingk® AS 2040

- For flexible sealants and screeds with very good cement- & bitumen-compatibility
- Suitable for flexible roof-coatings, water-proofing and crack-bridging
- EN 14891 capable waterproofing



Alberdingk® AS 2065

- Extremely compatible with cement and mortar
- Building emulsion
- Fillers, putties and levelling grouts
- Screeds
- Bonding layers and slurries



Albodur® 3003 VP

- The polyol is self-emulsifying in water, making it ideal for use in 3-component systems requiring maximum impact- and chemical resistance.



Alberdingk® ALBORapid 11

- Additive polymer which can significantly increase the drying speed of water based coatings. By adding 2.5 - 5% of the product (on polymer solids) to a coating, the drying under marginal conditions (low temperature and high humidity) is so much improved that an early rain resistance can be obtained.

For further information, please contact us:

Alberdingk Boley GmbH

Düsseldorfer Str. 53 | 47829 Krefeld | Germany

Tel.: +49 2151/528-0 | mailto: info@alberdingk-boley.de

or follow the QR-code:

